



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE
 5. PHOSPHOR BRONZE PER QQ-B-750
 6. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 7. TEFLON MIL-P-19468

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
9	SHELL		NOTE 1	NOTE 3	1 B50000-1-B
8	GASKET	RUBBER	RED		1 GS-115/8X15
7	RETAINER RING		NOTE 1	NOTE 3	1 B50000-5
6	SPRING	SK5		NOTE 4	1 B50000-6
5	WASHER		NOTE 2	NOTE 3	1 WS-128/9X08
4	BODY		NOTE 1	NOTE 3	1 SMAM-BM1-1
3	INSULATOR		NOTE 7	NATURAL	1 SMAM-BM1-2
2	CONTACT PIN		NOTE 5	NOTE 6	1 SMAF-BM1-2
1	BODY		NOTE 1	NOTE 3	1 SMAF-BF1-4

DIMENSIONS ARE IN MILLIMETERS			
UNLESS OTHERWISE SPECIFIED TOLERANCES			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	

PART NO.	SMAF-BM1-NT3G-50	
APPROVED	DATE	10-11-01'
CHECKED	DATE	10-11-01'
DRAWN	DATE	10-11-01'
FILE NO.		

Amphenol	
TITLE SMA FEMALE TO BNC MALE ADAPTOR	
DRAWING NO.	
ITEM NO.	

REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE