



MARKETING SALES DRAWING

DIMENSIONS IN INCHES - DO NOT SCALE THIS DRAWING
DIMENSIONS IN METRIC - []

This drawing is the property of Tusonix, Inc., and may not be used, reproduced, published or disclosed to others without expressed authorization by Tusonix Inc.

Electrical Testing
per Tusonix standard
test plans and Mil-Std-202
Test Methods.



SPECIFICATIONS

TUSONIX STYLE:	2499-003
Capacitance Value:	1000 pF
Capacitance Tolerance:	-0% +100%
Temp. Characteristics:	X5U
Rating:	500 WVDC @ 85 °C
Current (A):	20
IR Min @ 100 vdc	10 GΩ
DWV	1500 VDC
Operating Range:	-55° TO + 85°C

NOTES:

- SUPPLIED WITH SILVER PLATED HEX NUT AND INTERNAL TOOTH LOCK WASHER.
- TUSONIX STANDARD PART
 NUMBER: 2499-003-X5U0-102P.
 TUSONIX R.o.H.S. COMPLIANT PART
 NUMBER: 2499-003-X5U0-102P LF.
 CUSTOMER MUST SPECIFY STANDARD OR RoHS PART NUMBER WHEN ORDERING.
- PART MARKING: TRADEMARK, CAPACITANCE CODE AND TOLERANCE CODE STAMPED ON BUSHING HEX FLATS:
 STANDARD PART: BLACK MARKING.
 RoHS COMPLIANT PART: GREEN MARKING.

X-2015 Rev-0

REVISION RECORD	Original Release C.O. 20000508-4-01	0	DIM'S IN METRIC ADDED, SPEC. TABLE REVISED L.E. 01-27-04	ADDED NOTES 2 & 3. S.M. 10-21-05	1	20051021-1-01	2	DIM .051 METRIC WAS 1.29. S.M. 07-24-06	3	20060712-1-04	4	REDRAWN BUSHING WITH SHOULDER. S.M. 08-09-06	20060728-2-01	--TOLERANCES-- Unless Otherwise Specified	DECIMAL ± .015 [0.38]	ANGLES ± 	Title BUSHING TYPE FEED-THRU CAPACITOR	
	Drawn L.E. 05-09-00			Scale 3X														
	Approved T.C. 05-09-00																	
	TUSONIX TUCSON, ARIZONA																	
A															2499-003-X5U0-102P			