

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 25_716-50-7-2/003_-



Description

Straight panel cable jack, flange mount

Interface Standards
IEC 61169-4_CECC 22190_DIN 47223_VG 95250

Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 7.5 GHz

Mechanical Data

Centre contact crimped
Outer contact crimped
Weight 0.1113 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze / Brass	Silver Plating
Outer contact	Bronze	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	NR (Natural Rubber)	
Crimp ferrule	Brass	SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00008825
Catalogue drawing DCA-00008827
Assembly instruction DOC-0000179881
Mounting hole DOU-00008824

Ordering Information

Single package 25_716-50-7-2/003_-E
Bulk 100 pcs package 25_716-50-7-2/003_-H

Additional Information

Suitable cables RG_214_/U, GX_07272_D

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!
It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions