

COAXIAL TERMINATION, 50 Ohm, N, plug (male)

6560.17.AB

Properties

- Various bandwidth
- Impedance matched
- Standard or precision types
- Low and medium power



Product configuration		
Interface	Gender	Standard
N	plug (male)	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Electrical data	
Impedance	50Ω
Operating frequency	0 GHz ... 2 GHz
VSWR	1.1
Return loss	26.4 dB

Electrical Data (frequency related)		
Frequency range	VSWR max	Return loss
0 GHz to 2 GHz	1.1	

Electrical Data (power)	
Average power	60 W at 25 °C ambient temperature. Linearly derated to W at 150 °C ambient temperature.
Peak power	1500 W, 5 μs pulse width, 0.05 % duty cycle

Interface and material data		
Interface	N / plug (male)	
Piece parts	Material	Plating
Centre contact	Brass	Gold Plating (without Nickel underplating)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Aluminium	Anodized
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

COAXIAL TERMINATION, 50 Ohm, N, plug (male)

6560.17.AB

Interface and material data		
Gasket	VMQ (Silicone rubber)	
Piece parts	Material	Plating
Mechanical data		
Weight	0.325 kg	
Environmental data		
Operation temperature	-40 °C ... 150°C	
Ordering Information Table		
Item number	Item description	
22643799	6560.17.AB	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1705 / Date of publication: 09.11.2023 / uncontrolled copy