

Between Series Adaptor 34_MMBX-QN-50-1/1--_N

Description

Adaptor jack/jack
MMBX jack (female) / QN jack (female)

Interface standards
Series MMBX - SUHNER-MMBX
Series QN - QN QLF compliant



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz

Environmental Data

Operating temperature -55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

Material Data

Interface - MMBX jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Bronze	SUCOPRO / Gold Plating
Outer contact	Brass	SUCOPRO / Gold Plating
Body	Brass	SUCOPRO / Gold Plating
Insulator	LCP (Liquid crystal polymer)	

Interface - QN jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Bronze	SUCOPRO / Gold Plating
Outer contact	Brass	SUCOPLATE (R) / SUCOPRO Plating
Body	Brass	SUCOPLATE (R) / SUCOPRO Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing DOU-00088323

Ordering Information

Tray package 34_MMBX-QN-50-1/1--_NY