

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 25_BNC-50-1-6/133_N



Description

Straight panel cable jack, flange mount

Interface Standards

IEC 60169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 4 GHz

Mechanical Data

Centre contact crimped
Outer contact crimped
Weight 0.0155 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Piece Parts	Material
Centre contact	Copper Beryllium / Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Crimp ferrule	Copper

Surface Plating

Centre contact	Gold Plating (Nickel underplated)
Outer contact	SUCOPLATE (R) Plating
Body	SUCOPLATE (R) Plating
Crimp ferrule	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00008810
Catalogue drawing	DCA-00008813
Assembly instruction	DOC-0000179123

Ordering Information

Bulk 100 pcs package	25_BNC-50-1-6/133_NH
Single package	25_BNC-50-1-6/133_NE

Additional Information

Suitable cables	RG_178_B/U, RG_196_A/U
-----------------	------------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions