

# HUBER+SUHNER® DATA SHEET

## Coaxial PCB Connector: 84\_SMB-50-0-1/111\_N



### Description

Right angle PCB plug

Interface Standards

IEC 60169-10\_MIL-STD-348A/311\_CECC 22130

### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 4 GHz

#### Mechanical Data

Board mounting type through holes  
Weight 0.0035 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact  
Outer contact  
Body  
Insulator

##### Material

Copper Beryllium Alloy  
Brass  
Brass  
PFA / PTFE

##### Surface Plating

Gold Plating (Nickel underplated)  
Gold Plating (Nickel underplated)  
Gold Plating (Nickel underplated)

### Related Documents

Outline drawing DOU-00110760  
Catalogue drawing DCA-00012874

### Ordering Information

Bulk 100 pcs package 84\_SMB-50-0-1/111\_NH  
Single package 84\_SMB-50-0-1/111\_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**