

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 21_716-50-0-2/003_-



Description

Straight cable jack

Interface Standards

IEC 61169-4_CECC 22190_DIN 47223_VG 95250



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 7.5 GHz

Mechanical Data

Centre contact soldered
Weight 0.1021 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Bronze
Outer contact	Bronze
Body	Brass
Insulator	PFA / PTFE

Surface Plating

Silver Plating
Silver Plating
SUCOPLATE (R) Plating

Related Documents

Catalogue drawing DOU-00005933

Ordering Information

Single package	21_716-50-0-2/003_-E
Bulk 50 pcs package	21_716-50-0-2/003_-F

Additional Information

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions