

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 22\_H4-50-0-6/100\_N

Rev.: D



### Description

Straight bulkhead receptacle jack

Interface standards



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 0.3 GHz

#### Mechanical Data

Weight 0.0174 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) not compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Gasket	FPM
Fastening nut	Brass
Washer	Bronze

##### Surface Plating

Gold Plating (Nickel underplated)
Silver Plating
Silver Plating

Silver Plating
Silver Plating

#### Related Documents

Outline drawing	DOU-00069781
Catalogue drawing	DCA-00010178
Mounting hole	DOU-00008751

#### Ordering Information

Single package	22_H4-50-0-6/100_NE
----------------	---------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**

Document: DOC-0000187398 G

Issued: 30.10.07

Uncontrolled Copy

Page 1/1