




### Microwave performances :

RADIALL P/N	CONNECTORS	FREQUENCY RANGE (GHz)	VSWR Max				
			DC - 4	4 - 8	8 - 12.4	12.4 - 18	18 - 22
R404 210 6XX	SMA M	DC - 18 GHz	1.05+0.0125*F(GHz)			1.30	
R404 213 600	SMA M	DC - 22 GHz	1.05	1.15		1.20	1.30
R404 213 650	SMA M	DC - 22 GHz	1.05	1.15		1.20	1.30
R404 213 651	SMA M	DC - 22 GHz	1.05	1.15		1.20	1.30
R404 213 655	SMA M	DC - 22 GHz	1.05	1.15		1.20	1.30
R404 219 600	SMA F	DC - 22 GHz	1.05	1.15		1.25	1.30
R404 219 650	SMA F	DC - 22 GHz	1.05	1.15		1.25	1.30
R404 219 655	SMA F	DC - 22 GHz	1.05	1.15		1.25	1.30
R404 370 6XX	TNC M	DC - 18 GHz	1.08	1.10	1.15	1.20	
R404 280 651	SMA 2.9 M	DC - 40 GHz	1.30				
R404 285 651	SMA 2.9 F	DC - 40 GHz	1.30				



Part Number	A inch (mm)	B inch (mm)	Weight (g)
R404 210 600	.47" (12)	.25" (6.4)	3.5
R404 210 650			
R404 210 602			
R404 210 652			
R404 213 600	.65" (16.5)	.30 (7.7)	5
R404 213 650			
R404 213 651			
R404 213 655			
R404 219 600	.56" (14.3)		
R404 219 650			
R404 219 655			
R404 370 6xx	.99" (25)	.51 (13)	2.3
R404 280 651	.72" (18.4)	.30 (7.7)	5.5
R404 285 651	.76" (19.3)		