

HUBER+SUHNER® DATA SHEET

RF TERMINATION: Type 65_BNC-75-0-1

Rev.: E



Description

Standard Termination, Low Power

Product Configuration

Connector BNC plug (male)
Interface standard IEC 60169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data

Nominal impedance 75 Ω
Frequency range DC to 1 GHz
VSWR max. 1.1
Power rating 1 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature.
800 Watt peak power

Mechanical Data

Weight 0.014 kg

Environmental Data

2002/95/EC (RoHS) compliant

Material Data

Piece Part

Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Coupling nut	Brass

Surface Plating

Hard Au min. 1.3 μm over Ni min. 1.3 μm
SUCOPLATE (R) Plating
Sucoplate min. 0.5 μm over Ag min. 2 μm
Sucoplate min. 2 μm

Related Documents

Outline drawing DOU-00020116

Ordering Information

Single packaging 65_BNC-75-0-1/133_NE



HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions