

# Coaxial DC Block BNC

## BLK-222+

50Ω 10 MHz to 2.2 GHz

### Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
DC Input Voltage	100V Max.

Permanent damage may occur if any of these limits are exceeded.

### Features

- low insertion loss
- rugged unibody construction
- off-the-shelf availability



CASE STYLE: FF747


### Applications

- CATV
- test and measurement instrumentation
- communication systems
- defense systems

### +RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### Outline Drawing



### Electrical Specifications at 25°C

FREQUENCY (MHz)	INSERTION LOSS (dB)		RETURN LOSS (dB)	
	Typ.	Max.	Typ.	Min.
10 - 100	0.04	0.15	40	30
100 - 500	0.10	0.35	33	24
500 - 1000	0.16	0.45	33	22
1000 - 2200	0.22	0.70	27	14




### Outline Dimensions (inch/mm)

B	D	wt.
.62	1.94	grams
15.75	49.28	30.0

### Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)	Return Loss (dB)	
		Male	Female
10	0.02	39.66	39.85
50	0.03	46.56	47.48
100	0.04	40.04	40.53
250	0.06	33.62	34.65
400	0.10	30.87	32.73
500	0.12	29.76	31.77
600	0.13	29.11	31.19
750	0.15	28.58	30.94
900	0.15	28.29	30.72
1000	0.17	28.12	30.21
1200	0.18	27.32	28.71
1400	0.19	25.85	26.69
1500	0.20	24.97	25.75
1600	0.21	24.12	24.84
1800	0.23	22.51	23.09
1900	0.26	21.89	22.36
2200	0.27	20.50	20.60

### Electrical Schematic



**Mini-Circuits®**  
ISO 9001 ISO 14001 AS 9100 CERTIFIED  
The Design Engineers Search Engine Provides ACTUAL Data Instantly at [minicircuits.com](http://minicircuits.com)  
I/F/R/F MICROWAVE COMPONENTS

For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuits' applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp).

REV. OR  
M116139  
EDR-9082AUF1  
BLK-222+  
URJ/RAV  
121025  
Page 1 of 1