

# E-Series 4-Way 0° Power Divider

## 0.25 - 250 MHz

**ES-4-3**

V3.00

### Features

- 4 Way
- 0°

### Specifications @ 25°C

Frequency Range	0.25 - 250 MHz	
Insertion Loss	Typical	Maximum
	0.25 - 2.5 MHz	0.4 dB / 0.7 dB
	2.5 - 125 MHz	0.5 dB / 0.75 dB
	125 - 250 MHz	0.7 dB / 1.2 dB
Isolation	Typical	Minimum
	0.25 - 2.5 MHz	33 dB / 20 dB
	2.5 - 125 MHz	30 dB / 20 dB
	125 - 250 MHz	27 dB / 20 dB
Amplitude Unbalance	Maximum	
	0.25 - 2.5 MHz	0.15 dB
	2.5 - 125 MHz	0.2 dB
	125 - 250 MHz	0.25 dB
Phase Unbalance	Maximum	
	0.25 - 2.5 MHz	4°
	2.5 - 125 MHz	6°
	125 - 250 MHz	8°

### Operating Characteristics

Impedance	50 Ohms Nominal
-----------	-----------------


### Ordering Information

Part No. ES-4-3	Packaging Tube
--------------------	-------------------

### Absolute Maximum Ratings

Parameter	Absolute Maximum
Maximum Power Rating	1 Watt
Internal Load Dissipation	0.125 Watt
Pin Temp (10 sec)	260°C
Storage Temperature	-55°C to 100°C

### R-2



Dimensions in ( ) are in mm.  
Unless Otherwise Noted: .x = ±0.04 (1.00)  
.xx = ±0.02 (0.50)  
.xxx = ±0.010 (0.250)

WEIGHT (APPROX.): 0.23 OUNCES 6.3 GRAMS

### Pin Configuration

Function	Pin No.
Not Connected	3,5,6
Ground	3,5,6
Input	4
Port 1	7
Port 2	8
Port 3	1
Port 4	2

S 0335 B

Specifications Subject to Change Without Notice.

**M/A-COM, Inc.**

North America: Tel. (800) 366-2266 ■ Asia/Pacific: Tel. +81 (03) 3226-1671 ■ Europe: Tel. +44 (1344) 869 595  
Fax (800) 618-8883 Fax +81 (03) 3226-1451 Fax +44 (1344) 300 020