



## SPECIFICATIONS

Frequency Range:	10 - 3000 MHz
Isolation:	25 dB Min
Insertion Loss:	1.8 dB Max
Current <sup>1</sup> :	3000 mA Max
Power:	10 Watts Max
Voltage:	50 Vdc Max
VSWR:	1.50:1 Max

### Notes:

- Higher current and isolation requirements available.

## PIN-OUT TABLE

RF In (DC Blocked):	1
RF/DC Output:	3
DC In (Bias):	2
Ground:	Housing

**PULSAR** MICROWAVE CORPORATION

PULSAR MICROWAVE CORPORATION  
48 INDUSTRIAL WEST, CLIFTON NJ 07012  
TEL: 973-779-6262 FAX: 973-779-2727  
WWW.PULSARMICROWAVE.COM

DESCRIPTION :

Bias Tee

MODEL NO. :

BT-06-411

DIMENSIONS ARE IN INCHES  
DECIMAL TOLERANCE:  
2 PLACE ± .02  
3 PLACE ± .010

SIZE  
A

CAGE CODE :  
0HR85

REV CODE :

SCALE : N / A

ALL SPECIFICATIONS ARE SUBJECT TO  
CHANGE WITHOUT NOTICE AT ANY TIME

SHEET 1 OF 1