



**Part Number:** **T44-2**

Revision 20190524 - Generated 2019-May-30



<b>OD</b>	(nom. - bare core) (max. - after coating)	11.18 mm 11.68 mm	0.440 in 0.460 in
<b>ID</b>	(nom. - bare core) (min. - after coating)	5.82 mm 5.31 mm	0.229 in 0.209 in
<b>Ht</b>	(nom. - bare core) (max. - after coating)	4.04 mm 4.55 mm	0.159 in 0.179 in
<b>Mass</b>	(approximate)	1.3 grams	
<b>Magnetic Dimensions</b>	A <sub>e</sub> - Eff. Mag. Cross Section	0.0990 cm <sup>2</sup>	
	L <sub>e</sub> - Eff. Mag. Path Length	2.68 cm	
	V <sub>e</sub> - Eff. Core Volume	0.266 cm <sup>3</sup>	
	WA - Min. Eff. Window Area	0.221 cm <sup>2</sup>	
	sa - Surface Area	4.81 cm <sup>2</sup>	
<b>Inductance</b>	μ <sub>i</sub> (reference)	10	
	A <sub>L</sub> value (nominal)	5.2 nH/N <sup>2</sup>	
	Test Winding	N=100, #34 AWG	
	Frequency	1 MHz	
	Voltage on Agilent 4284A	1.0 V	
<b>Core Loss &amp; Q</b>	A <sub>L</sub> tolerance	±5%	
	Core Loss(mW/cm <sup>3</sup> )=	$\frac{f}{\frac{a}{B_{pk}^3} + \frac{b}{B_{pk}^{2.3}} + \frac{c}{B_{pk}^{1.65}}} + d \cdot B_{pk}^2 \cdot f^2$	
	where B <sub>pk</sub> expressed in gauss, f expressed in hertz, and:	a=4.00E+09, b=3.00E+08, c=2.70E+06, d=9.60E-16	
	Q test winding	N=100, #34 AWG	
	Q frequency	2 MHz	
<b>DC Saturation</b>	Q min on HP4342A	137	
	%μ <sub>i</sub> =	$\frac{1}{a + b \cdot H^c} + d$	
	where H expressed in oersteds, and:	a=1.00E-02, b=1.83E-07, c=1.46, d=0.00	
	H <sub>DC</sub>	200 Oe	
	Percent Initial Perm(nom.)	95.9%	
<b>Coating/Pkg</b>	Percent Initial Perm(min.)	94.8%	
	Coating Type:	Red/Clear Epoxy Paint	
	Voltage Breakdown (min.)	500 Vrms, 60Hz	
	Limit	3 mA, 5 s	
<b>Winding Table</b>	Package Quantity	10,000 Pcs/Box	
	Wire Size	AWG	18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38
<b>Single Layer</b>	mm	1.000, 0.800, 0.630, 0.500, 0.400, 0.315, 0.250, 0.200, 0.160, 0.125, 0.100	
	Turns	11, 14, 18, 23, 29, 37, 47, 59, 74, 93, 116	
<b>Full Winding</b>	Rdc(Ω)	4.2 m, 8.4 m, 17.3 m, 35.1 m, 70.3 m, 142.7 m, 288.3 m, 575.7 m, 1.1, 2.3, 4.6	
	Turns	10, 16, 25, 38, 59, 91, 141, 219, 339, 524, 812	
<b>Full Winding</b>	Rdc(Ω)	3.8 m, 9.6 m, 24.0 m, 58.0 m, 143.1 m, 351.0 m, 865.0 m, 2.1, 5.3, 12.9, 31.9	

