



| MECHANICAL SPECIFICATIONS |                                    |                 |                                    |                      |            |
|---------------------------|------------------------------------|-----------------|------------------------------------|----------------------|------------|
|                           | Type                               | Geometry        |                                    | Material & finishing |            |
| Connector 1               | N Jack Bulkhead                    | Straight        |                                    | Nickel-plated Brass  |            |
| Connector 2               | SMA Plug                           | Straight        |                                    | Gold-plated Brass    |            |
|                           | Type                               | Dielectric      | Jacket                             | Ext. diam.           | Op. Temp.  |
| Cable                     | RG223/U                            | PE              | PVC                                | 5.4 mm               | -25/+85 °C |
| ELECTRICAL SPECIFICATIONS |                                    |                 |                                    |                      |            |
| Frequency range           | DC – 6 GHz<br>VSWR 1.29 (18 dB RL) |                 | 6 – 11 GHz<br>VSWR 1.43 (15 dB RL) |                      |            |
| Impedance                 | 50 Ω                               |                 |                                    |                      |            |
| Frequency (MHz)           | Typical Attenuation (dB/m)         | Frequency (MHz) | Typical Attenuation (dB/m)         |                      |            |
| 50                        | 0.10                               | 2400            | 0.78                               |                      |            |
| 150                       | 0.18                               | 5500            | 1.27                               |                      |            |
| 450                       | 0.31                               | 8000            | 1.60                               |                      |            |
| 1000                      | 0.48                               | 10000           | 1.85                               |                      |            |

| Part #          | Standard length |
|-----------------|-----------------|
| N15S02-03-00250 | L = 25 cm       |
| N15S02-03-00500 | L = 50 cm       |
| N15S02-03-00750 | L = 75 cm       |
| N15S02-03-01000 | L = 100 cm      |
| N15S02-03-01500 | L = 150 cm      |
| N15S02-03-02000 | L = 200 cm      |
| N15S02-03-03000 | L = 300 cm      |

| Part #        | Custom length                     |
|---------------|-----------------------------------|
| N15S02-03-"L" | Replace L with cable length in mm |



www.qaxial.com



**N15S02-03 Series**