



MECHANICAL SPECIFICATIONS					
	Type	Geometry		Material & finishing	
Connector 1	N Plug	Straight		Nickel-plated Brass	
Connector 2	N Plug	Straight		Nickel-plated Brass	
	Type	Dielectric	Jacket	Ext. diam.	Op. Temp.
Cable	RG142B/U	PTFE	FEP	4.95 mm	-65/+165 °C
ELECTRICAL SPECIFICATIONS					
Frequency range	DC – 6 GHz VSWR 1.22 (20 dB RL)				
Impedance	50 Ω				
Frequency (MHz)	Typical Attenuation (dB/m)	Frequency (MHz)	Typical Attenuation (dB/m)		
50	0.09	1000	0.46		
150	0.16	2400	0.76		
450	0.29	5500	1.25		

Part #	Standard length
N02N02-05-00250	L = 25 cm
N02N02-05-00500	L = 50 cm
N02N02-05-00750	L = 75 cm
N02N02-05-01000	L = 100 cm
N02N02-05-01500	L = 150 cm
N02N02-05-02000	L = 200 cm
N02N02-05-03000	L = 300 cm

Part #	Custom length
N02N02-05-"L"	Replace L with cable length in mm



www.qaxial.com



# N02N02-05 Series