



MECHANICAL SPECIFICATIONS					
	Type	Geometry		Material & finishing	
Connector 1	SMA Plug	Straight		Gold-plated Brass	
Connector 2	SMA Plug	Straight		Gold-plated Brass	
	Type	Dielectric	Jacket	Ext. diam.	Op. Temp.
Cable	RG142B/U	PTFE	FEP	4.95 mm	-65/+165 °C
ELECTRICAL SPECIFICATIONS					
Frequency range	DC – 6 GHz VSWR 1.14 (24 dB RL)				
Impedance	50 Ω				
Frequency (MHz)	Typical Attenuation (dB/m)	Frequency (MHz)	Typical Attenuation (dB/m)		
50	0.09	1000	0.46		
150	0.16	2400	0.76		
450	0.29	5500	1.25		

Part #	Standard length
S02S02-05-00250	L = 25 cm
S02S02-05-00500	L = 50 cm
S02S02-05-00750	L = 75 cm
S02S02-05-01000	L = 100 cm
S02S02-05-01500	L = 150 cm
S02S02-05-02000	L = 200 cm
S02S02-05-03000	L = 300 cm

Part #	Custom length
S02S02-05-“L”	Replace L with cable length in mm



www.qaxial.com



S02S02-05 Series