



MECHANICAL SPECIFICATIONS					
	Type	Geometry		Material & finishing	
Connector 1	N Plug	Straight		Nickel-plated Brass	
Connector 2	N Jack Bulkhead	Straight		Nickel-plated Brass	
	Type	Dielectric	Jacket	Ext. diam.	Op. Temp.
Cable	LLF240 (LMR-240)	Foam PE	PVC	6.1 mm	-40/+80 °C
ELECTRICAL SPECIFICATIONS					
Frequency range	DC – 6 GHz VSWR 1.29 (18 dB RL)				
Impedance	50 Ω				
Frequency (MHz)	Typical Attenuation (dB/m)	Frequency (MHz)	Typical Attenuation (dB/m)		
50	0.06	1000	0.25		
150	0.10	2400	0.42		
450	0.17	5500	0.75		

Part #	Standard length
N02N15-22-00500	L = 50 cm
N02N15-22-00750	L = 75 cm
N02N15-22-01000	L = 1 m
N02N15-22-01500	L = 1.5 m
N02N15-22-02000	L = 2 m
N02N15-22-03000	L = 3 m
N02N15-22-04000	L = 4 m
N02N15-22-05000	L = 5 m
N02N15-22-10000	L = 10 m

Part #	Custom length
N02N15-22-"L"	Replace L with cable length in mm



www.qaxial.com



N02N15-22 Series