



MECHANICAL SPECIFICATIONS					
	Type	Geometry		Material & finishing	
Connector 1	BNC Plug	Straight		Nickel-plated Brass	
Connector 2	BNC Plug	Straight		Nickel-plated Brass	
	Type	Dielectric	Jacket	Ext. diam.	Op. Temp.
Cable	RG223/U	PE	PVC	5.4 mm	-25/+85 °C
ELECTRICAL SPECIFICATIONS					
Frequency range	DC – 4 GHz VSWR 1.22 (20 dB RL)				
Impedance	50 Ω				
Frequency (MHz)	Typical Attenuation (dB/m)	Frequency (MHz)	Typical Attenuation (dB/m)		
50	0.10	1000	0.48		
150	0.18	2400	0.78		
450	0.31	5500	1.27		

Part #	Standard length
B02B02-12-00250	L = 25 cm
B02B02-12-00500	L = 50 cm
B02B02-12-00750	L = 75 cm
B02B02-12-01000	L = 100 cm
B02B02-12-01500	L = 150 cm
B02B02-12-02000	L = 200 cm
B02B02-12-03000	L = 300 cm

Part #	Custom length
B02B02-12-"L"	Replace L with cable length in mm



www.qaxial.com



**B02B02-12 Series**