



#### MECHANICAL SPECIFICATIONS

	Type	Geometry	Material & finishing		
<b>Connector 1</b>	SMA Plug	Right Angle	Tri-metal plated Brass		
<b>Connector 2</b>	SMA Plug	Right Angle	Tri-metal plated Brass		
	Type	Dielectric	Jacket	Ext. diam.	Op. Temp.
<b>Cable</b>	RG316/D Dual Shield	PTFE	FEP	2.9 mm	-65/+165 °C

#### ELECTRICAL SPECIFICATIONS

<b>Frequency range</b>	DC – 6 GHz VSWR 1.22 (20 dB RL)
<b>Impedance</b>	50 Ω

Frequency (MHz)	Typical Attenuation (dB/m)	Frequency (MHz)	Typical Attenuation (dB/m)
50	0.18	1000	0.88
150	0.31	2400	1.43
450	0.55	5500	2.37

Part #	Standard length
S07S07-03-00100	L = 10 cm
S07S07-03-00150	L = 15 cm
S07S07-03-00200	L = 20 cm
S07S07-03-00300	L = 30 cm
S07S07-03-00400	L = 40 cm
S07S07-03-00500	L = 50 cm
S07S07-03-00750	L = 75 cm
S07S07-03-01000	L = 100 cm

Part #	Custom length
S07S07-03-"L"	Replace L with cable length in mm



www.qaxial.com



# S07S07-03 Series