



MECHANICAL SPECIFICATIONS					
	Type	Geometry		Material & finishing	
Connector 1	N Plug	Straight		Brass / SUCOPLATE®	
Connector 2	N Plug	Straight		Brass / SUCOPLATE®	
	Type	Dielectric	Jacket	Ext. diam.	Op. Temp.
Cable	S_04272_B	Foam-PE	PE	5.5 mm	-40/+85 °C
ELECTRICAL SPECIFICATIONS					
Frequency range	DC – 12.4 GHz VSWR ≤1.15 (RL ≥23 dB)	12.4 – 16 GHz VSWR ≤1.22 (RL ≥20 dB)	16 – 18 GHz VSWR ≤1.43 (RL ≥15 dB)		
Impedance	50 Ω				
Frequency (GHz)	Typical Attenuation (dB/m)	Frequency (GHz)	Typical Attenuation (dB/m)		
0.9	0.23	10.8	1.13		
2.7	0.45	12.6	1.27		
5.4	0.70	14.4	1.40		
8.1	0.93	18.0	1.65		

Part #	Standard length
N02N02-60-00500	L = 50 cm
N02N02-60-00600	L = 60 cm
N02N02-60-00750	L = 75 cm
N02N02-60-01000	L = 1 m
N02N02-60-01500	L = 1.5 m
N02N02-60-02000	L = 2 m
N02N02-60-05000	L = 5 m
N02N02-60-10000	L = 10 m

Part #	Custom length
N02N02-60-“L”	Replace L with cable length in mm



www.qaxial.com



N02N02-60 Series