




MECHANICAL SPECIFICATIONS

	Type	Geometry		Material & finishing	
Connector 1	SMA Plug	Right Angle		Gold-plated Brass	
Connector 2	SMA Jack Bulkhead	Straight		Gold-plated Brass	
	Type	Dielectric	Jacket	Ext. diam.	Op. Temp.
Cable	RG223/U	PE	PVC	5.4 mm	-25/+85 °C

ELECTRICAL SPECIFICATIONS

Frequency range	DC – 6 GHz VSWR ≤1.22 (RL ≥20 dB)		
Impedance	50 Ω		
Frequency (MHz)	Typical Attenuation (dB/m)	Frequency (MHz)	Typical Attenuation (dB/m)
10	0.04	450	0.31
50	0.09	1000	0.47
100	0.14	2400	0.77
150	0.18	5500	1.27



Part #	Standard length
S07S15-12-00250	L = 25 cm
S07S15-12-00500	L = 50 cm
S07S15-12-00750	L = 75 cm
S07S15-12-01000	L = 100 cm
S07S15-12-01500	L = 150 cm
S07S15-12-02000	L = 200 cm
S07S15-12-03000	L = 300 cm
Part #	Custom length
S07S15-12-"L"	Replace L with cable length in mm



www.qaxial.com

S07S15-12 Series