
RG142B/U Flexible Coaxial Cable Assembly



MECHANICAL SPECIFICATIONS					
	Туре	Geometry		Material & finishing	
Connector 1	N Plug	Right angle		Nickel-plated	Brass
Connector 2	N Plug	Right angle		Nickel-plated Brass	
	Туре	Dielectric	Jacket	Ext. diam.	Op. Temp.
Cable	RG142B/U	PTFE	FEP	4.95 mm	-65/+165 °C

ELECTRICAL SPECIFICATIONS

Frequency range	DC – 6 GHz
	VSWR ≤1.22 (RL ≥20 dB)
Impedance	50 Ω

Frequency	Typical Attenuation	Frequency	Typical Attenuation
(GHz)	(dB/m)	(GHz)	(dB/m)
50	0.09	1000	0.46
150	0.16	2400	0.76
450	0.29	5500	1.25

Part #	Length	Part #	Length
N07N07-05-00250	L = 25 cm	N07N07-05-0009N	L = 9 in
N07N07-05-00500	L = 50 cm	N07N07-05-0018N	L = 18 in
N07N07-05-00750	L = 75 cm	N07N07-05-0024N	L = 24 in
N07N07-05-01000	L = 100 cm	N07N07-05-0036N	L = 36 in
N07N07-05-01500	L = 150 cm	N07N07-05-0060N	L = 60 in
N07N07-05-02000	L = 200 cm	N07N07-05-0072N	L = 72 in
N07N07-05-03000	L = 300 cm	N07N07-05-0120N	L = 120 in

Part #	Custom lengths	
N07N07-05- L	Replace L with cable length in mm	
N07N07-05- L N	Replace L with cable length in in	



www.qaxial.com

N07N07-05 Series