

# COAXIAL ADAPTER, N, 50 Ohm, Bulkhead, jack / jack (female / female)

34\_N-50-0-1/133\_N

## Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration		
Interface type	Gender	Standard
N	jack (female)	IEC 61169-16_MIL-STD-348A/304_CECC 22210
N	jack (female)	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Interface and material data		
N		
<b>Piece parts</b>	<b>Material</b>	<b>Plating</b>
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating
N		
<b>Piece parts</b>	<b>Material</b>	<b>Plating</b>
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Body		SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	
Washer	Bronze	SUCOPLATE (R) Plating

Electrical data	
Impedance	50 Ω
Interface frequency	18 GHz

**COAXIAL ADAPTER, N, 50 Ohm, Bulkhead, jack / jack (female / female)**

34\_N-50-0-1/133\_N

<b>Mechanical data</b>	
Weight	0.0486 kg
Mating cycles	500

<b>Environmental data</b>	
Operation temperature	-65 °C ... 165°C

<b>Ordering Information Table</b>		
Item number	Item description	Packaging type
22542435	34_N-50-0-1/133_NE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2108 / Date of publication: 26.11.2023 / uncontrolled copy