

COAXIAL TERMINATION, 50 Ohm, N, jack (female)

6560.17.BB

Properties

- Various bandwidth
- Impedance matched
- Standard or precision types
- Low and medium power

**Product configuration**

Interface	Gender	Standard
N	jack (female)	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Electrical data

Impedance	50Ω
Operating frequency	0 GHz ... 2 GHz
VSWR	1.1
Return loss	26.4 dB

Electrical Data (frequency related)

Frequency range	VSWR max	Return loss
0 GHz to 2 GHz	1.1	

Electrical Data (power)

Average power	60 W at 25 °C ambient temperature. Linearly derated to W at 150 °C ambient temperature.
Peak power	1500 W, 5 μs pulse width, 0.05 % duty cycle
Electrical remarks	Mounted horizontally, convection cooled For input power not exceeding 100 mW, VSWR power coefficient typical 0,005/Watt.

Interface and material data

Interface	N / jack (female)	
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Aluminium	Anodized

COAXIAL TERMINATION, 50 Ohm, N, jack (female)

6560.17.BB

Interface and material data		
Insulator	PFA / PTFE	
Piece parts	Material	Plating
Mechanical data		
Weight	0.309 kg	
Environmental data		
Operation temperature	-40 °C ... 150°C	
Ordering Information Table		
Item number	Item description	
22643801	6560.17.BB	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1704 / Date of publication: 09.11.2023 / uncontrolled copy