



MECHANICAL SPECIFICATIONS

	Type	Geometry	Material & finishing		
Connector 1	SMA Plug	Straight	Passivated Stainless Steel		
Connector 2	SMA Jack	Straight	Passivated Stainless Steel		
	Type	Dielectric	Jacket	Ext. diam.	Op. Temp.
Cable	QF141	PTFE	FEP	4.00 mm	-55/+125 °C

ELECTRICAL SPECIFICATIONS

Frequency range	DC – 26.5 GHz VSWR ≤1.22 (RL ≥20 dB)				
Impedance	50 Ω				

Frequency (GHz)	Typical Attenuation (dB/m)	Frequency (GHz)	Typical Attenuation (dB/m)
1.5	0.48	12.0	1.69
4.0	0.84	16.0	2.00
6.0	1.08	18.0	2.16
10.0	1.48	26.5	2.80



Part #	Standard length
S22S32-76-00500	L = 50 cm
S22S32-76-00750	L = 75 cm
S22S32-76-01000	L = 100 cm
S22S32-76-01500	L = 150 cm
S22S32-76-02000	L = 200 cm
S22S32-76-03000	L = 300 cm
S22S32-76-04000	L = 400 cm
Part #	Custom length
S22S32-76-“L”	Replace L with cable length in mm



www.qaxial.com

S22S32-71 Series