## **Data Sheet**



# Coaxial Panel Connector 23\_QN-50-0-8/133\_N

### **Description**

Straight panel receptacle jack, flange mount

Interface standards QN QLF compliant

#### **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \mbox{Impedance} & \mbox{50} \ \Omega \\ \mbox{Interface frequency max.} & \mbox{11 GHz} \end{array}$ 

**Mechanical Data** 

Number of matings 100

**Environmental Data** 

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102) -40 °C to 125 °C compliant

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Bronze	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	

### **Related Documents**

Outline drawing DOU-00042451

### **Ordering Information**

Tray package 23\_QN-50-0-8/133\_NY

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.