


UNIT: mm (inch)

N PLUG

Cable marking options:

- <200 cm or 72" centered
- ≥200 cm or 72" one label per side
- Customized label or no label on request



RoHS
COMPLIANT

MECHANICAL SPECIFICATIONS

	Type	Geometry	Material & finishing		
Connector 1	N Plug	Straight	SUCOPLATE® Brass		
Connector 2	N Plug	Straight	SUCOPLATE® Brass		
	Type	Dielectric	Jacket	Ext. diam.	Op. Temp.
Cable	RG393/U	PTFE	FEP	9.90 mm	-65/+165 °C

ELECTRICAL SPECIFICATIONS

Frequency range	DC – 6 GHz VSWR ≤1.29 (RL ≥18 dB)
Impedance	50 Ω

Frequency (GHz)	Typical Attenuation (dB/m)	Frequency (GHz)	Typical Attenuation (dB/m)
50	0.05	1000	0.26
150	0.09	2400	0.44
450	0.16	5500	0.75

Part #	Length	Part #	Length
N02N02-07-00500	L = 50 cm	N02N02-07-0018N	L = 18 in
N02N02-07-00750	L = 75 cm	N02N02-07-0024N	L = 24 in
N02N02-07-01000	L = 100 cm	N02N02-07-0036N	L = 36 in
N02N02-07-01500	L = 150 cm	N02N02-07-0060N	L = 60 in
N02N02-07-02000	L = 200 cm	N02N02-07-0072N	L = 72 in
N02N02-07-03000	L = 300 cm	N02N02-07-0120N	L = 120 in
N02N02-07-04000	L = 400 cm	N02N02-07-0156N	L = 156 in
N02N02-07-05000	L = 500 cm	N02N02-07-0192N	L = 192 in
Part #	Custom lengths		
N02N02-07-L	Replace L with cable length in mm		
N02N02-07-LN	Replace L with cable length in in		

QAXIAL
QUALITY COAXIAL

www.qaxial.com

N02N02-07 Series