

Crimp BNC Male Coaxial Connector

BNC02-16-01

MECHANICAL SPECIFICATIONS		
Coaxial interface	BNC	
Gender	Male	
Standard	MIL-STD-348A	
Geometry	Straight	
Durability	>500 mating	
Centre/Outer attachment	Solder/Crimp	
Weight	14.5 g	
ELECTRICAL SPECIFICATIONS		
Impedance	75 Ω	
Frequency range	DC – 300 MHz	
VSWR	≤1.30	
Dielectric withs. voltage	500 V _{RMS}	
Insulation resistance	≥5000 MΩ	
MATERIAL SPECIFICATIONS		
COMPONENT	MATERIAL	FINISHING
Body, Nut	Brass	Nickel
Centre contact	Brass	Gold
Ferrule	Brass	Nickel
Insulator	PTFE	-
CABLE GROUOP		
RG180 / RG180A / RG195		
ENVIRONMENTAL SPECIFICATIONS		
Temperature range	-55 / +125 °C	
RoHS	Compliant (2011/65/EU RoHS 3)	
REACH	Compliant (EC 1907/2006)	



- KEY FEATURES**
- Characteristic Impedance 75 Ω
 - Fast Bayonet Mating
 - Robust and Reliable Industrial Design

