

WR-34 to 2.92mm (K) Female Adapter (Right Angle)

W34KF-U260R

PRODUCT SPECIFICATIONS		
Coaxial interface	2.92mm (K)	
Gender	Female	
Standard	MIL-STD-348A	
Waveguide interface	EIA	WR-34
	IEC	R260
Flange type	Square cover flange	
	EIA	-
	IEC	UBR-260
Geometry	Right angle	
ELECTRICAL SPECIFICATIONS		
Impedance	50 Ω	
Frequency range	21.7 – 33 GHz	
VSWR	≤1.20	
Insertion loss	≤0.3 dB	
MATERIAL SPECIFICATIONS		
COMPONENT	MATERIAL	FINISHING
Waveguide body	Brass	Gray paint
Connector body	Stainless steel	Passivated
Connector center pin	BeCu	Gold
ENVIRONMENTAL SPECIFICATIONS		
Temperature range	-40 / +70 °C	
RoHS	Compliant (2011/65/EU RoHS 3)	
REACH	Compliant (EC 1907/2006)	



KEY FEATURES

- Ka-band frequency band
- Low insertion loss, excellent matching
- Rugged, repeatable mechanical design
- 1-year standard warranty



DRAWING	Unit: mm

WR-34 to 2.92mm (K) Female Adapter (Right Angle)

W34KF-U260R

