N-Type Female to TNC Female Precision Coaxial Adapter

N-TNC40-PS

MECHANICAL SPECIFICATIONS		
Interface 1	N	
Gender 1	Female	
Standard 1	MIL-STD-348A	
Interface 2	TNC	
Gender 2	Female	
Standard 2	MIL-STD-348A	
Geometry	Straight	
Durability	≥500 mating	
Weight	29 g	
ELECTRICAL SPECIFICATIONS		
Impedance	50 Ω	
Frequency range	DC – 18 GHz	
VSWR	≤1.20	
Insertion loss	≤0.3 dB	
Working voltage	500 V_{RMS}	
Dielectric withs. voltage	1500 V_{RMS}	
Insulation resistance	≥5000 MΩ	
MATERIAL SPECIFICATIONS		
COMPONENT	**MATERIAL**	**FINISHING**
Body	Stainless steel	Passivated
Center contact	BeCu	Gold
Insulator	PEI / PTFE	-
ENVIRONMENTAL SPECIFICATIONS		
Temperature range	-55 / +165 °C	
RoHS	Compliant (2011/65/EU | RoHS 3)	
REACH	Compliant (EC 1907/2006)	




KEY FEATURES

- Precision microwave performance up to 18 GHz
- Low VSWR for high-frequency applications
- Passivated stainless steel construction
- Precision-machined interface geometry
- 1-year standard warranty

RoHS compliant

REACH

DRAWING **Unit: mm**




QAXIAL® is a registered trademark of Welco S.r.l.
ISO 9001:2015 certified | info@welcosrl.com

N-Type Female to TNC Female Precision Coaxial Adapter

N-TNC40-PS

TYPICAL PERFORMANCE (VSWR)



QAXIAL® is a registered trademark of Welco S.r.l.
ISO 9001:2015 certified | info@welcosrl.com