RP-SMA Female to SMA Female Coaxial Adapter

RPSMA-SMA40-01

MECHANICAL SPECIFICATIONS		
Interface 1	RP-SMA	
Gender 1	Female	
Standard 1	-	
Interface 2	SMA	
Gender 2	Female	
Standard 2	MIL-STD-348A	
Geometry	Straight	
Durability	>500 mating	
Weight	2.6 g	
ELECTRICAL SPECIFICATIONS		
Impedance	50 Ω	
Frequency range	DC – 18 GHz	
VSWR	≤1.20 @ 6 GHz	
Working voltage	335 V_{RMS}	
Dielectric withs. voltage	1000 V_{RMS}	
Insulation resistance	≥5000 MΩ	
MATERIAL SPECIFICATIONS		
COMPONENT	**MATERIAL**	**FINISHING**
Body	Brass	Gold
Center contact	BeCu	Gold
Insulator	PTFE	-
ENVIRONMENTAL SPECIFICATIONS		
Temperature range	-55 / +125 °C	
RoHS	Compliant (2011/65/EU | RoHS 3)	
REACH	Compliant (EC 1907/2006)	

KEY FEATURES

- DC to 18 GHz Operating Frequency Range
- Adapts RP-SMA to SMA Interfaces
- Robust and Reliable Industrial Design
- Consistent RF Performance

DRAWING

Unit: mm



QAXIAL® is a registered trademark of Welco S.r.l.
ISO 9001:2015 certified | info@welcosrl.com